

零件图	成品图	客户图
		○

REVISION DATA				
REV	ECN No.	DESCRIPTION	NAME	DATE
A0		NEW DRAWING	D.Y.Y	2023-04-08

Technical Data

Current rating:3A AC/DC.
Voltage rating:125V AC/DC
Temperature range:-40°C~+125°C.
Contact resistance:20mΩ Max.
Insulation resistance:1000MΩ Min.
Withstanding voltage: 500V AC/minute.
Material:
Housing:PA9T, UL94V-0
Pin:Phosphor Bronze

13	30.00	24.00	28.30	26.80
12	28.00	22.00	26.30	24.80
11	26.00	20.00	24.30	22.80
10	24.00	18.00	22.30	20.80
9	22.00	16.00	20.30	18.80
8	20.00	14.00	18.30	16.80
7	18.00	12.00	16.30	14.80
6	16.00	10.00	14.30	12.80
5	14.00	8.00	12.30	10.80
4	12.00	6.00	10.30	8.80
3	10.00	4.00	8.30	6.80
2	8.00	2.00	6.30	4.80
Poles	A	B	C	D

Recommended P.C.B Layout
General Tolerance±0.05

ANYCONN® 东莞市恩康电子科技有限公司
DONGGUAN ENKANG ELECTRONICS TECHNOLOGY CO.,LTD

www.enkcom.com
TEL:+86(0)769 8904 9672
FAX:+86(0)769 8904 9671
E-MAIL:sales@anyconn.com.tw

TOLERANCE	DATE : 2023-04-08	TITLE:
ANGLE ±5°	DRAWN : D.Y.Y	Wafer PH2.00 H9.20 Single Row
X.XXX ±0.15	CHECKED :	PART NO: WFBH11XXXXXXXXNH019
X.XX ±0.25	APPROVED :	
X.X ±0.38	PROJECTION	
X. ±0.50		REV: A0 UNIT: mm SCALE: 1:1 SIZE: A4 PAGE 1/1

WF	B	H	11	XXX	XX	X	X	N	H019
Pitch(mm) A 2.5 B 2.0 C 1.25 D 3.96 E 2.54 F 3.0 G 1.0	Angel Options R 90° D 180° S SMT H 卧式SMT	Product Type 11 Single row	No. of Positions XXX Poles	Pin Plating G0 Gold Flash SN Tin Plated T3 雾锡	Colour B Black W White N Natural	Insulator Material B PA66 D LCP F PA9T	W With peg N NO Peg L with lock T Fixed Tabs	Series NO.	

